

KNOW-HOW from P&S for YOUR ADVANTAGE.

# **HMT-S15**

cutting machine - standard





# The machine



The HMT-S15 is the standard machine in our product line for separating carbide and HSS. The production area lies between  $\emptyset$  3 mm -  $\emptyset$  40 mm. With a large and easy-to-load magazine, it is ideal for medium to large quantities. The best tried-and-tested P&S separation technology is installed.

**Loading and separation** 




- Manually insert the blanks into the magazine
- Diameter range measuring Ø 3 mm Ø 40 mm
- Bar length of max. 500 mm, cutting length of min. 5 mm max. 490 mm (one-sided)
- Enter the length and number of units required on the touch screen
- Close the safety door and start the machine
- The blank is separated and lifted into the prism

# **Cutting**



- The blank is positioned with the servo-driven axle
- Safe and secure grip via the hardened the prismatic guide and double-sided bar clamping
- · Optimal separation via the variable separating feed



#### Removal



- Once the separation process is complete, the separated blank is rolled off into a conveyor
- The bars are transported into the removal area via the conveyor
- Once the specified job has been completed, the machine moves to the home position



# **Options**



- Tip separation
- Magazine extension for bar lengths of 30 90 mm
- Magazine optimisation with partition plate and vibrator
- Partition plate for extending the magazine
- Automatic diameter control of cutting wheel
- Automatic cutting wheels sharpening unit
- Oil mist suction
- Compact fire protection system, Kraft & Bauer
- Coolant treatment system
- Coolant return pump tank

### **Overview**



- Long-lasting high-quality mechanical engineering
- Automatic diameter control
- Ease-of-use
- Different cutting lengths
- Optimum cooling increases service life
- Variable separating feed
- Separating feed secured by means of a sliding clutch
- Diameter range measuring Ø 3 mm Ø 40 mm
- Positioning accuracy ± 0.05 mm
- Bar lengths of min. 500 mm cutting length of min. 5 mm max. 490 mm (one-sided)



dewaxed rods cutting machine - cutting machine - chamfer grinding machine everything from a single source

# www.ps-maschinenbau.de





persönlich · leistungsstark · zuverlässig

P&S Maschinenbau GmbH Am Taschinger Berg 8 93413 Cham Germany Telefon +49 (0) 9971 39 27-0 Telefax +49 (0) 9971 39 27-27 E-Mail: info@ps-maschinenbau.de www.ps-maschinenbau.de

